



**LIBERATOR**  
**7MT24**

**S3 SRC**  
**EN ISO 20345:2011**  
**35 to 47**  
**High shoe**  
**Urban Sport**

**AIR FORCE**

**COMFORT**  
PLUS

**3D**Lining

Light **PLUS**

**TECHNO**  
LIGHT

**FLEX**system  
ZERO

**metal**  
**FREE**

- ⊗ High safety shoe, urban sport type, black colour.
- ⊗ Upper in finest quality black water-resistant leather, 1,9 / 2,1 thick. Anti-abrasion inserts. Lined throughout.
- ⊗ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Fastened by lacing . Laces black 130 cm.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ Back tab makes them easy to pull on.
- ⊗ Complete **CONFORT PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200J.

**Slip resistance tests results**

EN Standard : EN ISO 20345 : 2011 **Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,34** (>0,32) - On the heel **0,30** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,20** (>0,18) - On the heel : **0,16** (>0,13)

**Air Force sole** made of 100% polyurethane :

- ▶ Highly resistant to oils and hydrocarbons
- ▶ Highly resistant to abrasion
- ▶ Impact-Zone in the heel area for the optimal shock and micro-vibration
- ▶ Sporty design and linear profile



Weight	Gross Weight (42) : 1198 g / Net Weight (42) : 980 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	340 x 210 x 133		340 x 245 x 133	
Dimensions (mm)	680 x 215 x 350	680 x 425 x 350	685 x 500 x 350	685 x 250 x 350