

# SLIM

## 3-in-1 slim light

The ultra-thin, compact design of only ø9mm allows inspection in even the most inaccessible and narrow work areas. This makes the SLIM ideal for very demanding and difficult inspection jobs.

The new SLIM light is designed with a 100% foldable body. When fully folded the lamp can be used as a traditional hand-held work light. In folded position, the SLIM is reduced to pocket size - compact and portable to take with you everywhere.

The powerful 100 lumen spot light of the SLIM provides you with a flashlight function. As a unique feature, which has never been seen before, SLIM can be used as flashlight when the lamp is folded, providing a powerful flashlight with a handy, firm grip.

- 3-in-1: inspection light, work light and flashlight in one lamp
- Extremely powerful illumination up to 500 lumen with a powerful flashlight function
- Ultra slim and compact design
- Strong built-in magnet and hook for flexible positioning
- Choose between 2 light settings (50% or 100%) for maximized operating time

### TECHNICAL SPECIFICATIONS

COB LED/Spot: High power LED

Step 1/2

400/800 lux@0.5m

Spot: 4800 lux@0.5m

250/500 lumen


Spot: 100 lumen

2.5h/5h operating time

4.5h charging time

3.8V/2800 mAh Li-ion

IP30



**SLIM**

Item no. 03.5612

EAN: 5708997356128

EU DESIGN PATENT



**Scangrip Lighting**



**Declaration of Conformity**

Year in which CE Mark was first affixed: 2016

**We, Scangrip A/S**

Rytterhaven 9  
5700 Svendborg  
Denmark  
Phone no. +45 6320 6320

**Declare under our responsibility for the product:**

<b>Product Range:</b>	<b>BRAND:</b> SCANGRIP <b>NAME:</b> SLIM <b>DESCRIPTION:</b> Rechargeable LED Work light, Class III Charger: Input 100-240V AC 50/60Hz, Output 5V 1A DC Class II Battery: 3,8V 2800mAh Li-ion Specifications: Main light 250/500Lm RG1, Spot light 100Lm RG1 IP30, Temp -10° +40° C
<b>Product Code:</b>	03.5612

**The designated product is in conformity with the essential requirements of the following European Directives and harmonized standards:**

<b>Low Voltage Directive (LVD), 2014/35/EU</b> EN 60598-1:2015 EN 60598-2-4:1997 EN 62493:2010 EN 62471:2008  Charger: EN 61347-1:2008+A2:2013, EN61347-2-13:2006
---

<b>Electromagnetic compatibility Directive (EMC), 2014/30/EU</b> EN 55015:2013 EN 61547:2009 EN 61000-3-2:2014 EN 61000-3-3:2013  Charger: EN55015:2013, EN 61547:2009, EN 6100-3-2:2014, EN61000-3-3:2013
--

<b>Restriction of the use of certain Hazardous Substances in electrical and electronic equipment Directive (RoHS), 2011/65/EU</b> IEC 62321:2008 IEC 62321-5:2013 IEC 62321-6:2015
---

<b>Regulation (EC) no 1907/2006 of the European parliament and of the council of 18 December 2006 (REACH)</b> Substances of Very High Concern (SVHC) analysis, based on the list published by European chemicals agency (ECHA) for public consultation regarding regulation (EC) No.1907/2006 concerning the REACH.
--

**Date: 17.01.2017**

*Jasar Elezaj*  
Jasar Elezaj  
Quality Manager

Description	Details	Secondary Light	Main Light	Electrical	Operation	Product Line	Downloads	Videos
-------------	---------	-----------------	------------	------------	-----------	--------------	-----------	--------

Product Number	03.5612
EAN number	5708997356128
Product types	Hand Lamp
Net Weight (kg)	0.22
Length (mm)	165.00
Width (mm)	44.00
Height (mm)	28.00
Packaging	4-colour box
In the box	Lamp, Charger, Charge cable, Manual
Sales display included	Yes

Description	Details	Secondary Light	Main Light	Electrical	Operation	Product Line	Downloads	Videos
-------------	---------	-----------------	------------	------------	-----------	--------------	-----------	--------

Luminous Flux, Max (Lumen)	100
Illuminance, Max (Lux)	4800
Beam Angle (°)	25
CRI	>80
CCT	6000
Light Source Secondary	High power LED
Illuminance Distance (Meter)	0.50

Description	Details	Secondary Light	Main Light	Electrical	Operation	Product Line	Downloads	Videos
-------------	---------	-----------------	------------	------------	-----------	--------------	-----------	--------

Light Source	COB LED		
Luminous Flux, Max (Lumen)	500		
Luminous Flux, Min (Lumen)	250		
Illuminance, Max (Lux)	800		
Illuminance, Min (Lux)	400		
Illuminance Distance (Meter)	0.50		
CRI	Ra >80		
CCT (Kelvin)	6000		
Adjustable Light Output	2 levels		
Beam Angle Main	120°		
LED performance (lm/w)	155		

Description	Details	Secondary Light	Main Light	Electrical	Operation	Product Line	Downloads	Videos
-------------	---------	-----------------	------------	------------	-----------	--------------	-----------	--------

Power source	Rechargeable Battery		
Battery type	Li-ion		
Battery capacity (mAh)	2800		
Battery voltage (V)	3.80		
Cable	1 m USB to mini DC		
Charging voltage DC (V)	5.00		
Charging current (A)	1.00		
Charger included	Yes		
Charging input voltage (V)	100-240V AC 50/60Hz		
Plug type	Type C (Euro plug)		
Max Power Consumption (W)	4.00		

Description	Details	Secondary Light	Main Light	Electrical	Operation	Product Line	Downloads	Videos
-------------	---------	-----------------	------------	------------	-----------	--------------	-----------	--------

Operating time, up to (hours)	4.50		
Charging time (hours)	4.50		
Ingress protection	IP30		
Operating temperature	-10 °C to +40 °C		
Impact resistance (meter)	1.00		